

Mulcher - A Series






Mulcher - A Series

SPECIFICATIONS					
Model	HP/KW	"Y" Blade/ Straight Blade (Qty.)	Hammer (Qty.)	Weight (Kg/Lbs)	LWH
AG5Y/H-32/16	45-80/33.55-59.65	32/16	16	532/1153	2140/1150/1110
AG5Y/H-36/18	45-80/33.55-59.65	36/18	18	558/1230	3990/1150/1110
AG6Y/H-40/20	45-80/33.55-59.65	40/20	20	591/1303	5840/1150/1110
AG7Y/H-44/22	45-80/33.55-59.65	44/22	22	650/1433	7690/1150/1110

OPTIONS

• Available in Fixed as well as Hydraulic variants.





24 X 7 Service



SALIENT FEATURES

- Double shielded box frame.
- Central gearbox with free wheel clutch @540 rpm.
- External setting of the belts.
- Adjustable rear roller.
- Three point hitch, Category 1-2.
- 4 V-belts BX Type side transmission.

BENEFITS

- · Specially designed Flail Mower, keeping in mind the mulching requirements of sugarcane farmers
- Cavalo Mulcher's raised deck allows for easy shredding and mulching the farm residue of almost all crops.

Contact us

Navdurga Agri Implements Pvt. Ltd.

