

Laser Leveler - A Series



Think Farming, Think Cavallo





Think Farming, Think Cavalo

Laser Leveler - A Series

SPECIFICATIONS

DESCRIPTION	7Ft. DOUBLE AXLE
Working Width [mm]	2134
Bucket Plate Thickness [mm]	10
Cutting Blade Thickness [mm]	12
Weight [Kg. Approx]	735
Hydraulic Cylinder Bore	80 mm
Stroke	13 Inch
Distributor	Gates 20-25 LPM
Tractor Power [HP]	50 & Above
Length x Width x Height	3270 [10.75 ft] X 2154 [7 ft] X 2910 [9.5 ft]
Tyres	6-16 SL, Single Axle, Double Axle
Operating Range	Diameter 600-1000 m
Rotation Speed	600/700/800/900/1000 RPM +10%
Remote Control Range	500 Meter Approx.
LED Display	Laser Diode Red [635 nm]
Power Supply	12-24V DC
Operating Range	Diameter 600-900 m

SALIENT FEATURES

- Gear Box : Heavy duty gear box with Indian technology, gives long life and very low maintenance cost.
- Box Frame : High quality square tubes are used for strength, fitted with double spring multi lip oil seal.
- Levelling blades : Imported blades with optimised cutting angle for smooth running & easy levelling.
- Side transmission : Synchronised gear drive with good quality of gears made out of EN353, for heavy load and longer life.

ADVANTAGES

- Prepares farm bed in just one or two operations, saving about 40 % diesel & 60% time.
- Farm bed is ready for immediate sowing.
- Improved water management as bed preparation is very accurate so that moisture level is maintained.
- Cavalo laser leveler - A series can be used for any type of land like reaped sugarcane, banana, jute, dried grass etc.



Access to Spares



24 X 7 Service



1 Year Warranty*

Contact us

Navdurga Agri Implements Pvt. Ltd.



info@ndai.in



www.ndai.in



+91 8130061033